

# Façadeclip

For hidden fastening of façade wood

## Façadeclip

Black, electrogalvanised



Art. no.	Dimensions [mm] <sup>a)</sup>	Type	PU*
946010	5,5 x 115 x 15	F115 x 17	300
946012	5,5 x 115 x 15	F115 x 22	300
946013	5,5 x 115 x 15	F115 x 28	300
946014	5,5 x 130 x 15	F130 x 17	300
946015	5,5 x 130 x 15	F130 x 22	300
946016	5,5 x 130 x 15	F130 x 28	300
946017	5,5 x 145 x 15	F145 x 17	300
946018	5,5 x 145 x 15	F145 x 22	300
946019	5,5 x 145 x 15	F145 x 28	300

a) Height x length x width

\* Screws are included with this product

### Advantages

- For façade timbers with a profile height of 57–95 mm
- Hidden fastening
- Perfect constructive timber protection
- Ventilated façade system with spaced installation
- The façade timber's surface that is exposed to the weather remains undamaged
- Efficient and easy installation



## Technical data


Eurotec Façadeclip			Dimensions façade profile					Joint clearance between façade profiles		Quantity required Façade clips per m <sup>2</sup> Example	
Art. no.	Type	Dimensions [mm]			min.-max. height	min. strength	Assembly screw Length (L)	Fixing screw in hole A	Fixing screw in hole B	min. profile height	max. profile height
		H	W	L	[mm]	[mm]	[mm]	[mm]	[mm]	Stück	Stück
946010	F115 x 17	5,5	15	115	57 - 68	19	17	10	variable	28	24
946012	F115 x 22	5,5	15	115	57 - 68	24	22	10	variable	28	24
946013	F115 x 28	5,5	15	115	57 - 68	30	28	10	variable	28	24
946014	F130 x 17	5,5	15	130	68 - 80	19	17	10	variable	24	20
946015	F130 x 22	5,5	15	130	68 - 80	24	22	10	variable	24	20
946016	F130 x 28	5,5	15	130	68 - 80	30	28	10	variable	24	20
946017	F145 x 17	5,5	15	145	80 - 95	19	17	10	variable	20	18
946018	F145 x 22	5,5	15	145	80 - 95	24	22	10	variable	20	18
946019	F145 x 28	5,5	15	145	80 - 95	30	28	10	variable	20	18

Fastened to substructure with 4,5 x 29 mm fixing screw with drill point

Formula for determining quantity  
 $(1000 \text{ mm}/\text{substructure distance}) \times (1000 \text{ mm}/\text{bottom edge clearance}) = \text{pieces}/\text{m}^2$

600 mm substructure clearance  
 10 mm joint clearance

Please note: Before any work is carried out, all calculations must be checked and released by the responsible planner! For more information on this visit our homepage: [www.eurotec.team/en](http://www.eurotec.team/en)



### Efficient and easy installation

- Place Façadeclip on the back with stopper and insert assembly screws
- Repeat on all façade boards displaced
- Screw the façade wood to the counter-lathe with fixing screw
- Simply insert the next façade wood and screw on the top only with fixing screw
- The joint clearance is set automatically by the screw head of the fixing screw, that's it!

Each Façadeclip comes supplied with one 4,5 x 29 mm fixing screw with a drill point and two 4,2 x L assembly screws.

