


Concrete frame screw

Countersunk head, case-hardened steel




Art. no.	Dimensions [mm]	Drive	Thread	Head Ø [mm]	PU
B110061	7,5 x 42	TX30 ●	FT	11	100
B900903	7,5 x 52	TX30 ●	FT	11	100
B900620	7,5 x 62	TX30 ●	FT	11	100
B110062	7,5 x 72	TX30 ●	FT	11	100
B900621	7,5 x 82	TX30 ●	FT	11	100
B110063	7,5 x 92	TX30 ●	FT	11	100
B900896	7,5 x 102	TX30 ●	FT	11	100
B110064	7,5 x 112	TX30 ●	FT	11	100
B900724	7,5 x 122	TX30 ●	FT	11	100
B110065	7,5 x 132	TX30 ●	FT	11	100
B110066	7,5 x 152	TX30 ●	FT	11	100
B110067	7,5 x 182	TX30 ●	FT	11	100
B110068	7,5 x 212	TX30 ●	DT	11	100
B944642	7,5 x 232	TX30 ●	DT	11	100
B944638	7,5 x 252	TX30 ●	DT	11	100
B944643	7,5 x 272	TX30 ●	DT	11	100
B944639	7,5 x 302	TX30 ●	DT	11	100
B944641	7,5 x 342	TX30 ●	DT	11	100
B944644	7,5 x 372	TX30 ●	DT	11	100
B944645	7,5 x 402	TX30 ●	DT	11	100

FT = fully threaded, DT = double-threaded

Concrete frame screw

Pan head, galvanised steel



Art. no.	Dimensions [mm]	Drive	PU
B944661	7,5 x 42	TX30 ●	100
B944662	7,5 x 72	TX30 ●	100
B944663	7,5 x 82	TX30 ●	100
B944664	7,5 x 92	TX30 ●	100
B944665	7,5 x 112	TX30 ●	100
B944666	7,5 x 132	TX30 ●	100
B944667	7,5 x 152	TX30 ●	100
B944668	7,5 x 182	TX30 ●	100
B944669	7,5 x 212	TX30 ●	100

Mounting disc

Sendzimized steel



Art. no.	Plate-Ø [mm]	Ø Hole [mm]	PU
800308	40	7,35	—*

* On request

- Versatile mounting disc for secure and uniform load distribution
- Can be combined with different screws, nails and plugs

Mounting disc installation instructions

